

NEW PRODUCT!

# Bostik-Flex™ Plus

## Multi-Purpose Siliconized Acrylic Sealant



### DESCRIPTION

Bostik Bostik-Flex™ Plus is a high performance siliconized acrylic latex sealant with excellent adhesion to most building materials and common household surfaces. Bostik-Flex™ Plus complements multiple Bostik grout colors and is paintable with latex or oil based paints.

Bostik-Flex™ Plus has been developed for sealant applications including: windows, door frames, sinks, tubs, shower surrounds, countertops and bonding applications for wood trim, ceramic tile and natural stone.

### PRODUCT FEATURES

- Interior/exterior use
- Easy to apply and clean
- Excellent adhesion and elasticity for flexible joints
- Paintable after 1-2 hours
- Tools to a smooth finish
- Mold and mildew resistant
- Non-flammable and non-hazardous
- Use in non-submersible wet areas
- Contributes to LEED® certified projects

### SUBSTRATES

- Concrete
- OSB
- Wood
- Brick
- Plywood
- Drywall
- Gypsum Underlayment
- Ceramic Tile
- Stone
- Marble / Terrazo
- Concrete patch/SLU
- Well-Bonded Vinyl

### APPLICABLE STANDARDS

- Meets or exceeds the standard specification for elastomeric joint sealants ASTM C920-10, Class 25, Type S, Grade NS
- Meets or exceeds the standard specification for latex sealants ASTM C-834-10, Type OP, Grade -18°C
- Meets the requirements of AAMA 803.3-10

### PACKAGING

10.1 oz (299 mL) cartridges, 12 per case

For more information, contact us at:

1-800-726-7845 | [www.bostik.com/us](http://www.bostik.com/us)

T3149 - 09.21.17 - Read and understand data sheet completely before beginning installation.

### COVERAGE (Linear Feet per 10.1 Fl oz Cartridge)

| Depth | Width |      |      |      |
|-------|-------|------|------|------|
|       | 1/8"  | 1/4" | 3/8" | 1/2" |
| 1/8"  | 99    | 49   | 33   | 24   |
| 1/4"  | --    | 24   | 20   | 12   |
| 3/8"  | --    | --   | 11   | 8    |
| 1/2"  | --    | --   | --   | 6    |

### APPLICATION & PHYSICAL PROPERTIES

|                         |  |
|-------------------------|--|
| Ease of Gunning         | Easy   |
| Ease of Clean, Wet      | Easy   |
| Odor                    | Mild   |
| Open/Working Time**     | 15 min   |
| Movement Accommodations | +/- 25%  |
| Density                 | 1.44   |
| Application Temperature | 40°F to 90°F<br>(4°C to 32°C)  |
| Temperature Resistance  | -30°F to 170°F<br>(-34°C to 77°C)  |
| Full Cure Time          | 1-2 weeks  |
| Skinning Time           | 15 min @ 70°F (21°C)   |
| Shrinkage               | Approximately 30%  |
| Hardness                | Shore A 68   |
| Paintability            | With most paints   |
| Colors Available        | White, Sand Beige,<br>Delorean Gray,<br>Char Black, Antique White,<br>Monterey Red |

### LEED® CONTRIBUTION

|   |       |
|---|-------|
| EQ4.1: Low-Emitting Materials: VOC (as calculated per SCAQMD Rule 1168) | 0 g/L |
|---|-------|

\*\* Per ASTM E203-01 Standard Test Method for water using Volumetric Karl Fischer Titration Method. Results rounded to the nearest tenth. Test Method has error range of +/- 0.2%.

